Mastermax 3 Extra Roof Underlayment

Roof Underlayment

Description

Vapor-permeable and watertight function membrane with polypropylene layer protection on both sides.

Mastermax 3 Extra roof underlayment meets or exceeds all ASTM D226 and ASTM D4869 standards.

Usage

Vapor-permeable underlay for roofing. Used as a protective layer against moisture (liquid water penetration, wind-blow snow). The product is laid directly over the plywood or solid support, parallel to the eaves with minimum 10 cm (4 inch) overlapping and the printed side to the roof. The underlay is fixed to the plywood with roofing nails or nails with plastic cap.

Features

- Easy to install
- Prevents water from penetrating
- Remains breathable to permit unwanted moister escaping
- Maintains a cost-effective price point
- Greater tear than asphalt felt
- Slip-resistant surface
- Lightweight
- Use with asphaltic-shingle roof systems and slat and wood, metal, or tile

Benefits for installer

- Strong UV and heat protection
- Excellent water vapor transmission
- High tensile strength
- Easy installation

Packaging

Width per roll	1.5 m / 4.92 ft
Length per roll	50 m / 164.04 ft
Weight per roll	12.4 kg / 27.4 lb
Roll size	75 m² / 807.29 sq ft
Rolls per pallet	25
Product Code	MNH-3050

Storage

Under dry conditions, protected against atmospheric exposure, especially sun-radiation and other heat sources as well as against moisture.